²⁰²⁴ **KFX®50**







POWER

Engine	4-stroke, air-cooled, single
Displacement	49.5cc
Bore x Stroke	39 x 41.4mm
Compression Ratio	10.8:1
Maximum Torque	N/A
Fuel System	Keihin PTE16
Ignition	Solid state CDI
Transmission	Automatic CVT
Final Drive	2WD, Chain

Fuel Capacity	1.4 gal
Electronic Power Steering (EPS)	No
Turning Radius	8.9 ft
Towing Capacity	N/A
Total Rack Capacity	N/A
Rack Capacity, Front/Rear	N/A
Lighting	N/A

Double cradle, steel

27.2/27.6 in

DETAILS

Frame Type

Track Front/Rear

CAPABILITY

ay
rranty





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki's KFX®50 is recommended for use only by persons 6 or older, and the KFX®90 is recommended for use only by persons 10 and older. All children under 16 riding ATVs should always have direct adult supervision. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit el-salvador.kawasaki-la.com for full product details.