

2024

TERYX KRX® 4 1000 SE eS



POWER		Turning Radius	23.3 ft
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Displacement	999cc	Cargo Bed Load Capacity	351 lb
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Payload Capacity	1,001 lb
Bore x Stroke	92.0 x 75.1mm	Seating Capacity	4
Compression Ratio	11.5:1	Towing Capacity	N/A
Fuel System	DFI® with two 50mm throttle bodies	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Ignition	TCBI with Electronic Advance	DETAILS	
Starting System	Electric		
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)	Frame	Ladder type, tubular steel
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Overall Length	157.3 in
Engine Braking	Yes	Overall Width	68.1 in
CAPABILITY		Overall Height	79.3 in
		Curb Weight	2,207.2 lb* / 2,209.4 lb* CA Model
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Wheelbase	125.8 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Wheel Type	Alloy wheels
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Additional Features	Roof, Hifonics® Bluetooth®/AM/FM Audio System, WARN® VRX 45 Winch
Steering	Electric Power Steering (EPS) / rack-and-pinion	Color Choices	Metallic Flat Raw Graystone
Front Brakes	Dual hydraulic discs with two-piston calipers	Warranty	6 Month Limited Warranty
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	14.4 in (max), 13.6 in (std)		
Fuel Capacity	10.6 gal		



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit el-salvador.kawasaki-la.com for full product details.