BRUTE FORCE® 300









Conventional tie-rod

Nο

9.2 ft

500 lb

110 lb

44/66 lb

POWER

Engine 4-stroke, single-cylinder, SOHC, liquid-cooled

Displacement 271cc

Bore x Stroke 72.7 x 65.2mm

Compression Ratio 11.0:1

Maximum Torque 15.9 lb-ft @ 6,500 rpm

Fuel System Keihin CVK32 carburetor

DC-CDI Ignition

Transmission Automatic Continuously Variable Transmission (CVT)

with centrifugal clutch (H,L,N,R)

Final Drive 2WD, shaft

DETAILS

Overall Height

Lighting

Steering

Electronic Power

Steering (EPS)

Turning Radius

Towing Capacity

Rack Capacity, Front/Rear

Total Rack Capacity

Double-cradle, steel **Frame Type Tread Width** 33.5/32.7 in

Track Front/Rear 33.5/32.7 in

Overall Length 75.4 in

Overall Width 42.5 in

Seat Height 33.3 in

Curb Weight 535.8 lb*

Wheelbase 45.9 in

Instruments Speedometer, odometer, clock, fuel gauge, and coolant

(2) 35W headlights, 5W taillight, and 21W stoplight

Color Choices Grayish Blue, Timberline Green

46.1 in

12 Month Limited Warranty Warranty

CAPABILITY

Front Suspension / Independent double wishbone/5.2 in **Wheel Travel Rear Suspension /** Swingarm with single shock/5.6 in **Wheel Travel**

Front Tires AT 22 x 7-10 Maxxis® tubeless

Rear Tires AT 22 x 10-10 Maxxis® tubeless

Front Brakes Dual 148mm discs Single 148mm disc **Rear Brakes**

Ground Clearance 6.1 in **Starting System**

Electric

Fuel Capacity 3.2 gal

Scan with camera to view videos, key features and more.



