## **MULE SX™ 4x4**









## **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

**Maximum Torque** 21.4 lb-ft @ 2,400 rpm

**Bore x Stroke** 82.0 x 76.0mm

**Compression Ratio** 8.6:1

**Fuel System Fuel Injection** 

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** No

**Alternator Output** 22.9 amp

(max)

**Front Brakes** Drum **Rear Brakes** Drum **Ground Clearance** 6.7 in **Fuel Capacity** 4.2 gal **Turning Radius** 10.8 ft

Cargo Bed **Dimensions (LxWxH)** 

399 lb

35.6 x 40.9 x 9.6 in

**Cargo Bed Load** 

Capacity

**Payload Capacity** 915 lb

**Seating Capacity** 2

**Towing Capacity** 1,100 lb\*\*

Lighting (2) Halogen headlights, tail/brake lights

## **CAPABILITY**

Front Suspension / **Wheel Travel** 

MacPherson Strut/3.1 in

**Rear Suspension / Wheel Travel** 

Unit Swingarm/3.1 in

**Front Tires** 

24 x 9-10

**Rear Tires** 24 x 11-10

Steering Rack-and-pinion

**Park Brake Type** 

Independent, mechanical drum

## **DETAILS**

**Overall Length** 106.7 in

**Overall Width** 52.6 in

**Overall Height** 70.9 in

**Curb Weight** 1.031.9 lb\*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

**Color Choices** Super Black, Grayish Blue

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*\*Requires Optional Hitch

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.