



2025

TERYX® KRX4™ 1000

Kawasaki
Let the Good Times Roll®



-  METALLIC LIGHT GRAY/SUPER BLACK
-  METALLIC SIERRA BLUE/SUPER BLACK



POWER

| | |
|-------------------|---|
| Engine | 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled |
| Displacement | 999cc |
| Maximum Torque | 76.7 lb-ft @ 7,000 rpm |
| Bore x Stroke | 92.0 x 75.1mm |
| Compression Ratio | 11.5:1 |
| Fuel System | DFI® with (2) 50mm throttle bodies |
| Ignition | TCBI with Electronic Advance |
| Starting System | Electric |
| Transmission | Automatic CVT with centrifugal clutch (H,L,N,R) |
| Final Drive | Selectable 2WD/4WD with locking front differential, shaft |
| Engine Braking | Yes |

CAPABILITY

| | |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in |
| Rear Suspension / Wheel Travel | 4-link trailing-arm rear suspension, Showa 2.5 shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in |
| Front Tires | Maxxis® Carnivore 31 x 10.00R15 8PR |
| Rear Tires | Maxxis® Carnivore 31 x 10.00R15 8PR |
| Steering | Electric Power Steering (EPS) / rack-and-pinion |
| Front Brakes | Dual hydraulic discs with 2-piston calipers |
| Rear Brakes | Dual hydraulic discs with single-piston calipers |
| Ground Clearance | 14.8 in (max), 14.2 in (std) |
| Fuel Capacity | 10.6 gal |

| | |
|------------------------------|---|
| Turning Radius | 23.3 ft |
| Cargo Bed Dimensions (LxWxH) | 14.6 x 33.1 x 9.1 in |
| Cargo Bed Load Capacity | 351 lb |
| Payload Capacity | 1,001 lb |
| Seating Capacity | 4 |
| Towing Capacity | N/A |
| Lighting | (2) LED headlights, (2) LED taillights, LED stoplight |

DETAILS

| | |
|---------------------|--|
| Frame | Ladder type, tubular steel |
| Overall Length | 157.3 in |
| Overall Width | 68.1 in |
| Overall Height | 76.2 in |
| Curb Weight | 2,099.2 lb* / 2,101.4 lb* CA Model |
| Wheelbase | 125.8 in |
| Instruments | Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp |
| Additional Features | Steel skid-plates w/ drain holes |
| Color Choices | Metallic Light Gray/Super Black, Metallic Sierra Blue/Super Black |
| Warranty | 6 Month Limited Warranty |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit el-salvador.kawasaki-la.com for full product details.