## TERYX KRX® 1000 eS







D	n	W	C	D
Г	u	w	E	п

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement 999

Maximum Horsepower 110.0 hp¹ @ 8,500 rpm

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:

Fuel System DFI® with (2) 50mm throttle bodies

Ignition TCBI with electronic advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

## **CAPABILITY**

Front Suspension / Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks Wheel Travel with piggyback reservoir, fully adjustable preload, and KECS

controlled compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve
Wheel Travel Internal Bypass shocks with piggyback reservoir, fully adjustable
preload, and KECS controlled compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Steering Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

Rear Brakes 258mm dual hydraulic discs with single-piston calipers

Ground Clearance 14.4 in (max), 14.0 in (std)

Fuel Capacity 10.6 gal

Turning Radius 20.3 ft

Cargo Bed Dimensions 14.6 x 33.1 x 9.1 in (LxWxH)

351 lb

Cargo Bed Load

Capacity

Payload Capacity 781 lb

Seating Capacity 2

Towing Capacity N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

## **DETAILS**

Instruments

Frame Ladder type, tubular steel

Overall Length 132.1 in
Overall Width 68.1 in
Overall Height 77.0 in

Estimated Dry Weight 1,839.0 lb\*\* / 1,841.2 lb\*\* CA Model

Curb Weight 1,938.2 lb\* / 1,940.4 lb\* CA Model

Wheelbase 98.8 in

....

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

warning lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

Additional Features KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain holes,

TFT Full-Color Instrumentation with Smartphone Connectivity

Color Choices Sky Blue/Super Black
Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit el-salvador.kawasaki-la.com for full product details.