TERYX KRX® 1000 eS









POWER

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled Engine

Displacement

Maximum Horsepower 110.0 hp1 @ 8,500 rpm **Maximum Torque** 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

DETAILS

Lighting

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Frame Ladder type, tubular steel

20.3 ft

351 lb

781 lb

2

N/A

14.6 x 33.1 x 9.1 in

Overall Length 132.1 in **Overall Width** 68.1 in **Overall Height** 77 0 in

Estimated Dry Weight 1,839.0 lb** / 1,841.2 lb** CA Model **Curb Weight** 1.938.2 lb* / 1.940.4 lb* CA Model

Wheelbase

Multi-function digital meter with bar-style tachometer (2 display Instruments options), digital speedometer, bar-style fuel gauge, gear indicator

(2) LED headlights, (2) LED taillights, LED stoplight

(L, H, N, R), Power Mode, driving mode (2WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

warning lamp, and CVT belt warning lamp

Wheel Type Alloy with bead-lock wheels

KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain holes, **Additional Features**

TFT Full-Color Instrumentation with Smartphone Connectivity

Color Choices Sky Blue/Super Black 6 Month Limited Warranty Warrantv

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS

controlled compression damping/18.6 in

Rear Suspension / Wheel Travel

Steering

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable

preload, and KECS controlled compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Rear Tires Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

258mm dual hydraulic discs with single-piston calipers

14.4 in (max), 14.0 in (std)

Fuel Capacity 10.6 gal

Scan with camera to view videos. key features and more.

Ground Clearance



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit el-salvador.kawasaki-la.com for full product details.