## TERYX® KRX4™ 1000





SMOKY GRAY/SUPER BLACK



GRAYISH BLUE/SUPER BLACK





## **POWER**

Ignition

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement

Maximum Horsepower 110.0 hp1 @ 8,500 rpm **Maximum Torque** 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

**Compression Ratio** 

DFI® with (2) 50mm throttle bodies **Fuel System** 

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential, shaft

TCBI with electronic advance

**Engine Braking** Yes **Turning Radius** 23.3 ft

**Cargo Bed Dimensions** 14.6 x 33.1 x 9.1 in

(LxWxH)

Cargo Bed Load Capacity

351 lb

**Payload Capacity** 1.001 lb

**Seating Capacity** 

**Towing Capacity** N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

## **CAPABILITY**

Front Suspension / Double wishbone, Showa 2.5 shocks with piggyback reservoir, fully Wheel Travel adjustable preload, and 24-position adjustable compression

damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, Showa 2.5 shocks with Wheel Travel piggyback reservoir, fully adjustable preload, and 24-position

adjustable compression damping/21.1 in

**Front Tires** Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

**Rear Brakes** 258mm dual hydraulic discs with single-piston calipers

14.8 in (max), 14.2 in (std) **Ground Clearance** 

**Fuel Capacity** 10.6 gal

**DETAILS** 

Frame Ladder type, tubular steel

**Overall Length** 157.3 in **Overall Width** 68.1 in **Overall Height** 76.2 in

**Estimated Dry Weight** 1,997.7 lb\*\* / 1,999.9 lb\*\* CA Model

**Curb Weight** 2.099.2 lb\* / 2.101.4 lb\* CA Model

Wheelbase

Multi-function digital meter with bar-style tachometer (2 display Instruments options), digital speedometer, bar-style fuel gauge, gear indicator

(L, H, N, R), Power Mode, driving mode (2WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

warning lamp, and CVT belt warning lamp

**Wheel Type** Alloy

**Additional Features** Steel skid-plates w/ drain holes

**Color Choices** Smoky Gray/Super Black, Grayish Blue/Super Black

Warranty 6 Month Limited Warranty

Scan with camera to view videos, key features and more.

Steering



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit el-salvador.kawasaki-la.com for full product details.