TERYX® KRX4™ 1000 BLACKOUT EDITION









POTENCIA

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Cilindrada

Maximum Horsepower 110.0 hp1 @ 8,500 rpm Par motor máximo 75.2 lb-ft @ 7,000 rpm

Diámetro por carrer 92.0 x 75.1mm

Relación de compresión

DFI® with (2) 50mm throttle hodies Sistema de combustible

Ignition TCBI with electronic advance

Arrangue

Transmisión Automatic CVT with centrifugal clutch (H,L,N,R)

Transmisión final Selectable 2WD/4WD with locking front differential, shaft

Frenado del motor Yes Radio de giro 23.3 ft Dimensiones de la 14.6 x 33.1 x 9.1 in

plataforma de carga (L x An x AI)

Capacidad de la plataforma de carga

Capacidad de carga útil

Asientos

Capacidad de remolque

Cuadro

DETALLES

(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars

Ladder type, tubular steel

Largo total 160.4 in

Ancho total 68.1 in 78.0 in Altura total

Dry Weight 2,152.1 lb** / 2,154.3 lb** CA Model

351 lb

1,001 lb

Peso en orden de marcha 2.253.5 lb* / 2.257.7 lb* CA Model

Distancia entre eies 125 8 in

Instrumental Multi-function digital meter with bar-style tachometer (2 display

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp

Características

adicionales

LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics®

Audio System, WARN® VRX 45 Powersport Winch

Colores disponibles

Garantía Garantía limitada de 6 meses

CAPACIDAD

Suspensión delantera/

recorrido del neumático

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in

Electric Power Steering (EPS) / rack-and-pinion

258mm dual hydraulic discs with single-piston calipers

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with Suspensión trasera/

recorrido del neumático piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

13.8 in (max), 13.2 in (std)

Maxxis® Carnivore 31 x 10 00R15 8PR

Neumáticos delanteros

Neumáticos traseros Maxxis® Carnivore 31 x 10.00R15 8PR

Wheel Type

Dirección

Aleación

Frenos delanteros 258mm dual hydraulic discs with 2-piston calipers

Distancia al suelo

videos, característ-

icas clave v más.

Frenos traseros

Depósito de combustible



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite el-salvador.kawasaki-la.com para obtener detalles completos del producto.